













A conventional power socket is sufficient.



Product Details

| Height | 200 cm |
|----------------------|--|
| Total height | 800 cm |
| Covered area | Ø 886 cm |
| Pack size LxWxH | 100x140x90 cm |
| Weight | 110 kg |
| Assembly/Disassembly | within 5 minutes |
| Production time | approx. 3 weeks from order confirmation |
| Printing | sublimation print on the outer surface (included in the price) |

| Textile Properties | Oxford 500D |
|--------------------------------|---------------------|
| Water column (DIN EN 20811) | 1,600 mm |
| Light fastness | blue scale: 4.5-6.5 |
| (DIN EN ISO 105-B02) | (of max. 8) |
| Fire protection class | B - s1, d0 |
| (DIN EN 13501-1:2018) | (flame-retardant) |

Your Benefits

- 5 years manufacturer's warranty on material and production defects
- 2 years warranty on the motor
- high quality materials

Fastening

- For fastening the inflatable with guy ropes and pegs, it has flaps with eyelets.
- Make sure that you place the product on an appropriate, solid surface. The pegs must be firmly anchored in the ground.
- If the ground is too loose (sand, gravel or similar) and no pegs can be attached, 160 kg weights must be placed at each fixing point.
- Only use the product at wind speeds of max. 38 km/h.

