



Data Sheet


Kokon

Made in Europe



220 V continuous blower

A conventional power socket is sufficient.



Product Details

Height	310 cm
Total height	475 cm
Covered area	630x495 cm
Pack size LxWxH	100x140x90 cm
Weight	91 kg
Assembly/Disassembly	within 5 minutes
Production time	approx. 3 weeks from order confirmation
Printing	sublimation print on the outer surface (included in the price)

Textile Properties

Water column (DIN EN 20811)	1,600 mm
Light fastness (DIN EN ISO 105-B02)	blue scale: 4.5-6.5 (of max. 8)
Fire protection class (DIN EN 13501-1:2018)	B - s1, d0 (flame-retardant)

Oxford 500D

Water column (DIN EN 20811)	1,600 mm
Light fastness (DIN EN ISO 105-B02)	blue scale: 4.5-6.5 (of max. 8)
Fire protection class (DIN EN 13501-1:2018)	B - s1, d0 (flame-retardant)

Your Benefits

- 5 years manufacturer's warranty on material and production defects
- 2 years warranty on the motor
- high quality materials

Fastening

- For fastening the inflatable with guy ropes and pegs, it has flaps with eyelets.
- Make sure that you place the product on an appropriate, solid surface. The pegs must be firmly anchored in the ground.
- If the ground is too loose (sand, gravel or similar) and no pegs can be attached, 160 kg weights must be placed at each fixing point.
- Only use the product at wind speeds of max. 38 km/h.

